



■外形尺寸和印记 Outline Dimensions and Mark

DO - 214AA(SMB)



inch (mm)

■特征 Features

- I_o 2.0A
- V_{RRM} 20V-100V
- 耐正向浪涌电流能力高
High surge current capability
- 封装: 模压塑料
Cases: Molded plastic

■用途 Applications

- 整流用 Rectifier

■极限值 (绝对最大额定值)

Limiting Values (Absolute Maximum Rating)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Conditions	SS 22	SS 23	SS 24	SS 25	SS 26	SS 29	SS 210
反向重复峰值电压 Repetitive Peak Reverse Voltage	V_{RRM}	V		20	30	40	50	60	90	100
正向平均电流 Average Forward Current	$I_{F(AV)}$	A	正弦半波 60Hz, 电阻负载, TL(Fig.1) 60HZ Half-sine wave, Resistance load, TL(Fig.1)						2.0	
正向(不重复)浪涌电流 Surge(Non-repetitive)Forward Current	I_{FSM}	A	正弦半波 60Hz, 一个周期, $T_a=25^\circ C$ 60Hz Half-sine wave, 1 cycle, $T_a = 25^\circ C$						50	
结温 Junction Temperature	T_J	°C				-55~+125			-55~+150	
储存温度 Storage Temperature	T_{STG}	°C							-55 ~ +150	

■电特性 ($T_a=25^\circ C$ 除非另有规定)Electrical Characteristics ($T_a=25^\circ C$ Unless otherwise specified)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Condition	SS 22	SS 23	SS 24	SS 25	SS 26	SS 29	SS 210	
正向峰值电压 Peak Forward Voltage	V_F	V	$I_F=2.0A$		0.55		0.70		0.85		
反向漏电流 Peak Reverse Current	I_{R1}	mA	$V_{RM}=V_{RRM}$	$T_a=25^\circ C$	0.5			0.1			
	I_{R2}				10		5.0				
热阻(典型) Thermal Resistance(Typical)	$R_{\theta J-A}$	°C/W	结和环境之间 Between junction and ambient		75 ¹⁾						
	$R_{\theta J-L}$		结和终端之间 Between junction and terminal		17 ¹⁾						

备注: Notes:

¹⁾ 热阻从结到环境及从结到引线, 在电路板的0.3" x 0.3" (8.0毫米 x 8.0毫米)铜垫片区

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3" x 0.3" (8.0 mm x 8.0 mm) copper pad areas

■特性曲线(典型)

